

MACHINES FOR WORLD CLASS CLEANING AND DISINFECTION

PESUTEKNC

PHARMACEUTICAL INDUSTRY

A H T I



ISO 9001, 14001 and 18001 compliant  
Manufactured according to cGMP principles.

**AAA**<sup>®</sup>  
Highest Creditworthiness  
©Soliditet 2012

# AHTI

## Versatility and efficiency for the most demanding applications



### Wash cabinet volume

- 2.00 m<sup>3</sup>

### Washing temperature range

- +40°C to +85°C

### Noise level

- 66 dB

### Dimensions

- W 1358 D 1610 H 2045 (mm)

### Weight

- 795 kg

### Construction

- Acidproof steel AISI 316

### Other

- Cabinet for 2x20 l detergent canister

- Possibility to separate clean and dirty –areas (1-2 doors)
- Washing temperature adjustable between +40°C to +85°C
- Effective drying system
- User configurable programs (10 programs & 12 steps)
- Touch panel
- Fan operated vapour outlet
- Distilled and washing water sample outlet
- Electrically controlled door locks
- Twin powerfull wash pumps
- Compressed air connection for drying the machine internal tubes etc.

*AHTI is capable to clean and disinfect a wide range of the machinery parts, cylindrical items, tubes, hoses, bins etc. Utilizing 2 doors machine has possibility to separate the clean and dirty areas. By tailoring different wagon-equipment solutions AHTI can offer a long life span & good value for the investment.*

## CONNECTIONS

### Inlet water

- 3/4" connector
- Max +85°C warm water
- Cold water inlet 3/4"
- Distilled water inlet 3/4"

### Compressed air

- 1/2" connector

### Drain

- ø 51 mm tube, air operated valve

### Electrical

- Std. Voltage 3 x 400 V 50 Hz
- Other voltages available
- Fuse 3 x 63 A
- Power 43 kW
- Optional frequency optional 60 Hz
- 4 or 5 wire supply available

AHTI meets high level hygiene requirements for different applications in medical industry with its outstanding cleaning features.

*With AHTI you have one less item to worry about.*

